


CNSPC-7010-SOU

Installation Cable Cat.5e, U/UTP, 4P, 125 MHz, PVC, 305 m



Description

Cat.5e, U/UTP cable. 100 Ohm impedance. Data transmission frequencies of up to 125 MHz.

Technical Data

Standardisation	ISO/IEC 11801 2nd ed.; IEC 61156-5 2nd ed.; EN 50173-1; EN 50288-3-1; EIA/TIA 568B.2
Category	Cat.5e
Cable class	Installation Cable
Cu cable shielding	U/UTP
Number of fibers / conductors	8
Stranding	4P
Cable overall diameter	Ø 5.1 mm
Conductor type	tight buffer
Fiber / conductor diameter	AWG 24
Length (meter)	305
Cable jacket material	PVC
Cable jacket characteristics	cable, metal-free
Cable jacket characteristics	flame-retardant
Cable protection	no protection
Color code RAL	7035
Color	light gray

HONG KONG (HK) Limited

Unit 1303, 13/F, Beverly House, 93-107 Lockhart Road, Wanchai, Hong Kong.
 香港灣仔駱克道93107-號利臨大廈13樓1303室

Tel. : (852) 28639635 Fax : (852) 21296534 Mob.: (86) 18218762001

EGYPT

15 Sakalia St., From Makram Abeer, 3rd Floor, Nasr City, Cairo, Egypt.

Tel. : +202 2671 8862 / 3 Fax : +202 2275 2976 Mob. : +2012 2213 3810