

CNSPC-7020-SOU

Installation Cable Cat.6, U/UTP, 4P, 450 MHz, PVC, 305 m



Description

Cat.6, U/UTP cable. 100 Ohm impedance. Data transmission frequencies of up to 450 MHz.

Technical Data

Standardisation	ISO/IEC 11801 2nd ed.; IEC 61156-5 2nd ed.; EN 50173-1; EN 50288-6-1; EIA/TIA 568B.2.1
Category	Cat.6
Cable class	Installation Cable
Cu cable shielding	U/UTP
Number of fibers / conductors	8
Stranding	4P
Cable overall diameter	Ø 6.3 mm
Conductor type	tight buffer
Fiber / conductor diameter	AWG 23
Length (meter)	305
Cable jacket material	PVC
Cable jacket characteristics	cable, metal-free
Cable jacket characteristics	flame-retardant
Cable protection	no protection
Color code RAL	7035
Color	light gray

HONG KONG (HK) Limited

Unit 1303, 13/F, Beverly House, 93 -107 Lockhart Road, Wanchai, Hong Kong.
 香港灣仔駱克道93107-號利臨大廈13樓1303室

Tel. : (852) 28639635 **Fax** : (852) 21296534 **Mob.**: (86) 18218762001

EGYPT

15 Sakalia St., From Makram Abeed, 3rd Floor, Nasr City, Cairo, Egypt.

Tel. : +202 2671 8862 / 3 **Fax** : +202 2275 2976 **Mob.**: +2012 2213 3810