

CNSPC-7030-SOU Installation Cable Real10 Cat.6A, U/UTP, 4P, 650 MHz, PVC, Ø 9.0mm, 305 m



Description

Real10 Cat.6A, U/UTP cable. 100 Ohm impedance. Data transmission frequencies of up to 650 MHz.

Technical Data

Standardisation	ISO/IEC 11801 ed. 2.2; IEC 61156-5 2nd ed.; EN 50173-1; EN 50288-6-1; EIA/TIA 568-C.2
Cable class	Installation Cable
Cu cable shielding	U/UTP
Number of fibers / conductors	8
Stranding	4P
Cable overall diameter	Ø 9.0 mm
Fiber / conductor diameter	AWG 23
Length (meter)	305
Cable jacket material	PVC
Cable jacket characteristics	cable, metal-free
Cable jacket characteristics	flame-retardant
Cable protection	no protection

HONG KONG (HK) Limited

Unit 1303, 13/F, Beverly House, 93 - 107 Lockhart Road, Wanchai, Hong Kong.
香港灣仔駱克道93-107號利臨大廈13樓1303室

Tel. : (852) 28639635 **Fax** : (852) 21296534 **Mob.** : (86) 18218762001

EGYPT

15 Sakalia St., From Makram Abeer, 3rd Floor, Nasr City, Cairo, Egypt.

Tel. : +202 2671 8862 / 3 **Fax** : +202 2275 2976 **Mob.** : +2012 2213 3810