

CM ODF - A TYPE

12C-24C-36C-288C



*METAL HOUSE:

1:Smoked pull type design, it can optimize operation, ease of installation, inspection and testing. Unique detachable ear plate for easy installation and protection of products.Front transparent PC plastic panel, easy to observe the internal situation.

2: In the fiber patch panel Nylon fiber distribution frame of the coiling ring can support redundant optical fiber, and keep the bending radius of the fiber

3:Can install optional melt flange To manage and protect welding or mechanical cable termination

4:Material: A) Rack/Cold-rolled steel,thickness 1.2mm




5:Surface finish: Powder Plating

6:Functional Qualification Tests(Optical and Mechanical performance)

Description:

SIZE:	2U*19 "	3U*19 "		4U*19 "	8U*19 "
Max port:	36	72	96	144	288
Material:	Rack/Cold-rolled steel,thickness 1.2mm				
Optional design:	SC/LC/FC...				
Cable import /export:	4 port (2pcs at rear+ 2 pcs on the side)				
Operating temperature:	-40Oc to 70Oc				

Unique design:

Transparent baffle design	
Detachable ear plate design	
Full standard schematic	

Annotation configuration:

fiber rack	1pc
ear plate	2pcs
PC transparent plate	1pc
Plug at rear	2pcs
Plug on the side	2pcs

Optional configuration: (See the full picture)

yellow velcros
black velcros
fiber tray
adapter ---APC (Insertion loss: < 0.3 db)
wiring post
cable clamp
12fibers pigtail ---APC (Insertion loss: < 0.3 db, Return loss: > 60 db)
fiber heat shrink sleeve
cable tie
PE protection tube

Packing: 1PC/bubble bag + inner box, 3PCS/outer box